



Dept
Qty
DC 1
ED 1
IE 1
ISO 1
PD 1
R&D 1
SD 1
QA 1
QC 1
QE 1

CONNFLY Electronic Co., Ltd. and its confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights of CONNFLY Electronic Co., Ltd. are strictly protected. Any modification is strictly prohibited without prior written consent from CONNFLY. All intellectual properties provided herein are for reference purposes only and does not constitute authorization of its use in any format or manner. CONNFLY may enforce its intellectual property rights at its own discretion; failures or delays to exercise such rights does not constitute a waiver of such rights.

Assembly




Assembly V/T type




Assembly Right Angle


Male





Male V/T type



Male Right Angle



Famale



GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°
DRAWING TYPE		CUSTOMER	
SCALE	1:1	SHEET	1 OF 4
DRAWING NO.	C-DS1110-60-XXXXXXX-A		

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	WPY 10/08/24'		

Note:

1. Rated voltage:300V-400V
2. Rated current:10A-45A
3. insulation resistance:2000MΩ
4. Withstand voltage:1500V
5. Operating temperature: -30℃ to +90℃
6. Wiring method: Screw

Materials:

1. Shell material: PA66
2. Insulation material: PPS
High temperature resistance 260℃
3. Contact material: Copper gold plating

Product Number Code:

DS1110-60-X X X X X X X


- Mounting type
R:Elbow V:straight connector
- Cable diameter:
1:8-12mm 2:12-16mm
- Install Type
A:A Type
- Contact Plating
8:Gold flash
- Color of nut
U:Blue
- Color of housing
B:Black
- No. of Contacts
2 3 4 5 6 7 9

PROJECTION	TITLE	ø28 waterproof aviation plug docking type(Screw type)	
UNITS	mm		
SHEET SIZE	A4	SERIES	DS1110-60 Series
 晨翔电子有限公司 CONNFLY CONNFLY ELECTRONIC CO. LTD			


Dept
Qty
DC 1
ED 1
IE 1
ISO 1
PD 1
R&D 1
SD 1
QA 1
QC 1
QE 1

The information provided herein is from CONNFLY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights are reserved by CONNFLY Electronic Co., Ltd. All intellectual properties provided herein are for reference purposes only and does not constitute authorization of its use in any format or manner. CONNFLY may enforce its intellectual property rights at its own discretion; failures or delays to exercise such rights does not constitute a waiver of such rights.



Assembly




Assembly V/T type
Male





Male V/T type
Female



Male Right Angle



Assembly Right Angle



Suggested Panel Opening

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	WPY 10/08/24'		

Note:

1. Rated voltage:300V-400V
2. Rated current:10A-45A
3. insulation resistance:2000MΩ
4. Withstand voltage:1500V
5. Operating temperature: -30℃ to +90℃
6. Wiring method: Screw

Materials:

1. Shell material: PA66
2. Insulation material: PPS
- High temperature resistance 260℃
3. Contact material: Copper gold plating

Product Number Code:

DS1110-60-X X X X X X X

- Mounting type
R:Elbow V:straight connector
Cable diameter:
1:8-12mm 2:12-16mm
Install Type
A:A Type
Contact Plating
8:Gold flash
Color of nut
U:Blue
Color of housing
B:Black
No. of Contacts
2 3 4 5 6 7 9

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°
DRAWING TYPE		CUSTOMER	
SCALE	1:1	SHEET	2 OF 4
DRAWING NO.	C-DS1110-60-XXXXXXX-A		


PROJECTION	TITLE	Ø28 waterproof aviation plug rear nut type(Screw type)
UNITS	mm	
SHEET SIZE	A4	SERIES DS1110-60 Series

晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO. LTD

Dept
Qty
DC 1
ED 1
IE 1
ISO 1
PD 1
R&D 1
SD 1
QA 1
QC 1
QE 1


The information provided herein is from CONNFLY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights of CONNFLY Electronic Co., Ltd. are reserved. All intellectual properties provided herein are for reference purposes only and does not constitute authorization of its use in any format or manner. CONNFLY may enforce its intellectual property rights at its own discretion; failures or delays to exercise such rights does not constitute a waiver of such rights.

Assembly





Assembly V/T type

Male




Male V/T type




Famale



Assembly Right Angle



Male Right Angle



Suggested Panel Opening

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°
DRAWING TYPE		CUSTOMER	
SCALE	1:1	SHEET	3 OF 4
DRAWING NO.	C-DS1110-60-XXXXXXX-A		

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	WPY 10/08/24'		

Note:

1. Rated voltage:300V-400V
2. Rated current:10A-45A
3. insulation resistance:2000MΩ
4. Withstand voltage:1500V
5. Operating temperature: -30℃ to +90℃
6. Wiring method: Screw

Materials:

1. Shell material: PA66
2. Insulation material: PPS
High temperature resistance 260℃
3. Contact material: Copper gold plating

Product Number Code:

DS1110-60-X X X X X X X

- Mounting type
R:Elbow V:straight connector
- Cable diameter:
1:8-12mm 2:12-16mm
- Install Type
A:A Type
- Contact Plating
8:Gold flash
- Color of nut
U:Blue
- Color of housing
B:Black
- No. of Contacts
2 3 4 5 6 7 9

PROJECTION		TITLE	Ø28 waterproof aviation plug
UNITS	mm		square disc type(Screw type)
SHEET SIZE	A4	SERIES	DS1110-60series
晨翔电子有限公司 CONNFLY CONNFLY ELECTRONIC CO. LTD			

