


REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	WPY 03/06/26'		




NOTES:


Standard UL
 Rated voltage:400V
 Rated current:32A
 Wire range:0.5mm²-4.0mm²(Hard);
 0.5mm²-2.5mm²(Soft)
 Temp.Range:-40°C~+105°C
 Steip Length:(9-10)mm
 Box size:17.4*9.9*2.2CM
 Materials:
 Contact: Copper Alloy,Nature.
 Insulator: Nylon.
 Spring: Stainless steel.
 Product Number Code:
 DS1165-14-BOX-01

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION	TITLE	One-in Multiple-out Quick-connect Terminal Splitter Set	
X.	±0.30	X.	±2°	mm			
.X	±0.20	.X	±1°	A4	SERIES	DS1165-14 Series	
.XX	±0.15	.XX	±0.5°				
DRAWING TYPE		CUSTOMER DRAWING		 晨翔电子有限公司 CONNPLY CONNPLY ELECTRONIC CO. LTD			
SCALE		1:1	SHEET 1 OF 2				
DRAWING NO.		C-DS1165-14-BOX-01-A					

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	WPY 03/06/26'		




12.5±0.5




17.1±0.5



21.7±0.5




26.3±0.5




21±0.5

14.4±0.5




φ4.3
4.6±0.1

1T1




φ4.3
9.2
4.6±0.1

1T2



φ4.3
13.8
4.6±0.1

1T3



φ4.3
18.4
4.6±0.1

1T4

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE	One-in Multiple-out Quick-connect Terminal Splitter	
X.	±0.30	X.	±2°	UNITS	mm	SERIES	DS1165-14 Series	
.X	±0.20	.X	±1°					
.XX	±0.15	.XX	±0.5°					
DRAWING TYPE		CUSTOMER DRAWING		晨翔电子有限公司 CONFLY CONNFLY ELECTRONIC CO. LTD				
SCALE	1:1	SHEET	2 OF 2					
DRAWING NO.	C-DS1165-14-BOX-01-A							