

Female

Materials:

1. Insulating material: Thermoplastic, UL94 V-0.
2. Contact: Red Copper, Tin plated T=0.4mm.
3. Stop-off ring: SUS301
4. Sealing: Silicone rubber, Red.

Product Number Code:

DS1185-12 - X X X X X X

- Current Type
A: 30A
- Packing Type
1: Mix packing (Female+Male/Bag)
2: Separation packing (Female/Bag or Male/Bag)
Q: N*Female/Bag+N*Male/Bag+N*Male Contact/Bag
+Female Contact/Bag
- Housing color
B: Black
- Contact plating
6: Tin
- Mounting type
C: Locking type
- Connector type
F: Female M: Male
A: Female+Male

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE	Solar Connectors Wire to Wire	
X.	±0.60	X.	±5°	UNITS	mm		W/ Lock Type (1500V)	
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES	DS1185-12 SERIES	
.XX	±0.25	.XX	±2°	 晨翔电子有限公司 CONNFLY CONNFLY ELECTRONIC CO. LTD				
DRAWING TYPE		CUSTOMER						
SCALE	1:1	SHEET	1 OF 1					
DRAWING NO.	C-DS1185-12-XXXXX-A							