

Dept	
Qty	
DC	1
ED	1
IE	1
ISO	1
PD	1
R&D	1
SD	1
QA	1
QC	1
QE	1

The information provided herein is from CONNPLY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights of CONNPLY Electronic Co., Ltd. are strictly protected. All intellectual properties provided herein are for reference purposes only and does not constitute authorization of its use in any format or manner. CONNPLY may enforce its intellectual property rights at its own discretion; failures or delays to exercise such rights does not constitute a waiver of such rights.

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	WPY 02/28/26'		

Notes:

1. Input: MC4 (15-60V)
2. Output: Type-C (supporting CC/CV mode) 5V, 9V, 12V, 15V-3A, 20V-3.25A, 65W Max
3. Input under-voltage protection, output over-current protection, output short-circuit protection, and over-temperature protection

Product Number Code:

DS1206-01-X X

Product model:  
1:Type1  
Maximum power:  
65:65W

In the working state, the first line of the OLED screen displays the real-time output power. The second line of the screen scrolls through information such as output voltage, output current, internal temperature, and status code.



GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE	65W solar charger C-type output photovoltaic PD converter	
X.	±0.60	X.	±5°	UNITS	mm			
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES	DS1206-01 SERIES	
.XX	±0.25	.XX	±2°	<b>晨翔电子有限公司</b> <b>CONNPLY CONNPLY ELECTRONIC CO. LTD</b>				
DRAWING TYPE		CUSTOMER						
SCALE		1:1	SHEET 1 OF 1					
DRAWING NO.		C-DS1206-01-X-A						