

A	Dept	
	Qty	
	DC	1
	ED	1
	IE	1
	ISO	1
B	PD	1
	R&D	1
	SD	1
	QA	1
	QC	1
	QE	1

NOTES:
 Rated voltage:1500V/DC.
 Rated current:300A(95mm²) Max.
 Temp.Range:-40°C~+125°C.
 Protection grade:IP67.

Materials:
 Contact: Copper Alloy,Ag plated.
 Insulator: Nylon.
 Sealings: Silicone
 Product Number Code:

Rated voltage:1500V/DC.
Rated current:300A(95mm²) Max.
Temp.Range:-40°C~+125°C.
Protection grade:IP67.

Contact: Copper Alloy, Ag plated.

Sealings: Silicone

DS1207-03 - X X X X X X

— Rated current
250:250A 300:300A
350:350A



GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°
DRAWING TYPE		CUSTOMER	
SCALE	1:1	SHEET	3 OF 3
DRAWING NO.	C-DS1207-03-XXXXXX-A		

 晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO. LTD



 晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO. LTD