

Dept

Qty

DC

1

ED

1

IE

1

ISO

1

PD

1

R&D

1

SD

1

QA

1

QC

1

QE

1

1

2

3

4

5

6

7

8

REV.

DESCRIPTION

DRAWN

CHECKED

APPROVED

A

NEW RELEASE

WPY 06/23/26'

LED indicator light

PVC Wire

XT60

1 Red

2 Black

26

78.5

90

L±30

25

Note:

Specifications:

1.Fuse specification: 15A

2.Rated voltage: 12-24V

3.Output powerPower:150W

Materials:

1.Cable sheath:PVC

2.XT60 Housing:PA66

3.Contact:Gold-plated brass

Product Number Code:

DS1226-04-X X X X

Length(DIM L):

050:500mm 100:1000mm ...

Wire gauge:

1:14AWG 2:16AWG 3:18AWG

Contact Plating(XT60):

8:Full Gold Flash

Connector type:

P:Plug

(Serties Image-Reference Only)

GENERAL TOLERANCE

ANGLE TOLERANCE

PROJECTION

TITLE

Cigarette lighter plug to power connector extension cord

X. ±0.60

X. ±5°

UNITS

mm

.X ±0.38

.X ±3°

SHEET SIZE

A4

.XX ±0.25

.XX ±2°

SERIES

DS1226-04 Series

DRAWING TYPE

CUSTOMER

SCALE

1:1

SHEET

1 OF 1

DRAWING NO.

C-DS1226-04-XXXX-A

晨翔电子有限公司

CONNFLY CONNFLY ELECTRONIC CO. LTD